

INTELLIGENT SERIES


4inch Industrial Barcode Printer



GI-2408T PLUS

KEY FEATURES

- Preinstalled multiple printing emulations for easy integration
- Easy to load print media and ribbon, auto calibrate the print media
- Rugged and reliable construction, ideal for high volume label printing
- High-quality touch screen brings user a smart, intuitive and convenient operation experience



INTELLIGENT SERIES 4" Industrial Thermal Transfer Barcode Printer

MODEL	GI-2408T PLUS	GI-3406T PLUS	GI-2408T PLUS	GI-3406T PLUS
Level	Standard	Standard	Empower	Empower
Resolution	8dots/mm (203DPI)	12dots/mm (300DPI)	8dots/mm (203DPI)	12dots/mm (300DPI)
Printing Method	Thermal Transfer & Direct Thermal			
Max. print speed	203mm(8")/second	152mm(6")/second	203mm(10")/second	177.8mm(7")/second
Max. print width	104 mm (4.1 ")	108.4 mm (4.27")	104 mm (4.1 ")	108.4 mm (4.27")
Memory RAM	128 MB SDRAM			
Memory ROM	128 MB Flash Memory			
Interface	<ul style="list-style-type: none"> • USB 2.0 High Speed 480Mbps • USB Host 2.0, for scanner or PC keyboard • RS-232 • GPIO(factory option) 		<ul style="list-style-type: none"> • Internal Ethernet 10/100Mbps • Internal Bluetooth 4.0 (factory option) • Internal WiFi (factory option) 	
Power	Input: AC 90-240V, 1.5A, 50-60Hz, Output: DC 24V, 5A, 120W			
Internal fonts	<ul style="list-style-type: none"> • 8 alpha-numeric bitmap fonts • True type font engine (need download scalable font file) 			
1D Barcode	Code 11, Code 39, Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF14, MSI Plessey, PostCode, Telepen			
2D Barcode	QR Code, Micro QR Code, PDF417, Micro PDF417, Grid Matrix, MaxiCode, Aztec Code, Data Matrix			
Rotation	Font and barcode support 0, 90, 180, 270 degree			
Printer language	Compatible to TSPL, EPL, EPL 2, ZPL, ZPL II, DPL			
Physical dimension	260mm (W) * 335mm (H) * 439mm (D)			
Net Weight	12.8kg			

Applications

- Logistics
- Shipping
- Manufacturing
- Retail
- Warehousing
- Transportation

Environmental concern

Comply with RoHS, REACH, WEEE

Environment condition

Operation: 5 ~ 40°C, 25 ~ 85% non-condensing
Storage: -40 ~ 60°C, 10 ~ 90% non-condensing

Safety regulation

FCC Class A, CE Class A, CCC, BIS, CB

Accessories

- Windows labeling software CD disk
- Quick start guide
- USB cable
- Power cord
- 1" ribbon spindle x 2 for 450M ribbon

