

GV-2408D

4" Desktop Direct Thermal Label Printer



Key Features

- 203.2mm (8") per second print speed for 203 dpi.
- Internally scalable True type font engine.
- Firmware emulates the following: TSPL, EPL, EPL 2, ZPL, ZPL II, DPL.
- Provides Windows printer utility, Windows SDK, and Android SDK.
- Solutions for retail POS, shelf labeling, office applications, and shipping.

POWERFUL | HIGH PERFORMANCE | AFFORDABLE

4" Desktop Direct Thermal Label Printer

MODEL	GV-2408D
Printing method	Direct Thermal
Resolution	8 dots/mm(203DPI)
Print speed	203.2mm(8")/second
Print width	104 mm(4.1")
Interface	· USB 2.0 Full Speed 12Mbps · Ethernet 10/100Mbps (Factory option) · Internal Bluetooth 4.2 (Factory option) · Internal Wi-Fi (Factory option)
Memory RAM	16 MB SDRAM
Memory ROM	16 MB Flash
1D Barcode	Code 11, Code 39, Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF14, MSI Pleassy, PostCode, Telepen
2D Barcode	QR Code, Micro QR Code, PDF417, Micro PDF417, Grid Matrix, MaxiCode, Aztec Code, Data Matrix
User Interface	1 power switch, 2 buttons (Feed & Pause) 2 LEDs (Online, Error)
Sensors	Head open sensor, Reflective sensor (Moveable), Transmissive sensor (Moveable)
Label roll capacity	127mm (5")OD
Printer language	Compatible to TSPL, EPL, EPL 2, ZPL, ZPL II, DPL
Media type	Continuous, die-cut, black mark, fan-fold, notched (Outside wound)
Dimension	245mm (L) *186mm (W) *178mm (H)
Net weight	1.56kg



Environment concern

Comply with RoHS, REACH, WEEE

Certification

FCC, CE, CCC, BIS, CB

Application Industries



Healthcare



Shelf labeling



Large Retailer



Retail



Shipping



Shopping Mall