



GA-2408T

APEX SERIES

4 Inch Desktop Barcode Printer



Key Feature

- High-performance barcode printer with rich expansion capabilities
- Thermal transfer and thermal dual-mode automatic switching
- Fast 8 IPS print speed at 203 dpi print resolution, 6 IPS at 300 dpi version (GA-3406T)
- Pre-installed multiple emulation for easy system integration (EPL, EPL 2, ZPL, ZPL II, DPL, TSPL)
- Flexible connectivity: USB + Ethernet as standard
- RFID version works with jewelry label, flexible anti-metal RFID asset label, as factory option
- Bartender Ultralite available to edit and print your labels
- Driver, SDK, user guide, video, FAE support available



Peeler



Cutter





APEX SERIES

4 Inch Direct Thermal & Thermal Transfer Barcode Printer

MODEL	GA-2408T	GA-3406T
Level	Standard	Standard
Resolution	8dots/mm (203DPI)	12dots/mm (300DPI)
Max. Print Speed	203mm (8")/Second	152mm (6")/Second
Max. Print Width	104mm (4.09")	108.4mm (4.27")
Max. Print Length	15,000 mm(600")	6800mm (267.7")
Printing Method	Thermal Transfer & Direct Thermal	
Printer language	Compatible to TSPL, EPL, ZPL, ZPL II, DPL	
Interface	· USB 2.0 High Speed 480Mbps · Internal Ethernet 10/ 100Mbps · RS-232 (Distributor Optional) · Internal Bluetooth 4.0 (Distributor Optional) · Internal Wi-Fi (Distributor Optional)	
Internal fonts	· 8 alpha-numeric bitmap fonts · True type font engine (need download scalable font file)	
Rotation	Font and barcode support 0, 90, 180, 270 degree	
1D Barcode	Code 11, Code 39, Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF14, MSI Plessey, PostCode, Telepen	
2D Barcode	QR Code, Micro QR Code, PDF417, Micro PDF417, MaxiCode, Aztec Code, Data Matrix	
Dealer Option	· Cutter (Optional) · Peeler (Optional)	
Power	· Input: AC 100-240V, 50-60Hz. · Output: DC 24V, 2.5A, 60W	
Physical Dimension	190mm(W) * 198.3mm(H) * 280mm(D)	
Net Weight	2.3kg	

Certification

FCC Class A, CE Class A, CCC, BIS, CB

Environment concern

Comply with RoHS, REACH, WEEE

Accessories

- Windows Label Editing Software, Driver
- 1" ribbon spindle x 2 (for 300m ribbon)
- Quick Installation Guide
- External universal switching power supply
- Power Cord
- USB Cable

