

# INTELLIGENT SERIES

## 4 Inch Industrial Barcode Printer



## GI-2408T PLUS

### KEY FEATURES

- Rugged and reliable construction, built for high volume label printing
- Easy to load print media and ribbon, easy to operate, auto calibration
- Large capacity for 450m ribbon and industrial-grade print media
- Flexible connectivity options: USB+RS-232+Ethernet+3\*USB Host standard
- Compatible with various printing languages: TSPL, ZPL, ZPL-II, EPL, DPL
- Distributor choice: auto cutter, label peeler
- Bartender Ultralite available to edit and print your labels
- Driver, SDK, user guide, video, FAE support available



| MODEL              | GI-2408T PLUS                                                                                                                                                                    | GI-3406T PLUS                                                                                                                                                                 |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Level              | Standard                                                                                                                                                                         | Standard                                                                                                                                                                      |
| Resolution         | 8dots/mm (203DPI)                                                                                                                                                                | 12dots/mm (300DPI)                                                                                                                                                            |
| Printing Method    | Thermal Transfer & Direct Thermal                                                                                                                                                |                                                                                                                                                                               |
| Max. print speed   | 203mm(8")/second                                                                                                                                                                 | 152mm(6")/second                                                                                                                                                              |
| Max. print width   | 104mm (4.1")                                                                                                                                                                     | 108.4mm (4.27")                                                                                                                                                               |
| Interface          | <ul style="list-style-type: none"> <li>• USB 2.0 High Speed 480Mbps</li> <li>• USB Host 2.0, for scanner or PC keyboard</li> <li>• RS-232      • GPIO(factory option)</li> </ul> | <ul style="list-style-type: none"> <li>• Internal Ethernet 10/100Mbps</li> <li>• Internal Bluetooth 4.0 (factory option)</li> <li>• Internal WiFi (factory option)</li> </ul> |
| Power              | Input: AC 90-240V, 1.5A, 50-60Hz, Output: DC 24V, 5A, 120W                                                                                                                       |                                                                                                                                                                               |
| Internal fonts     | <ul style="list-style-type: none"> <li>• 8 alpha-numeric bitmap fonts</li> <li>• True type font engine (need download scalable font file)</li> </ul>                             |                                                                                                                                                                               |
| 1D Barcode         | Code 11, Code 39, Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF14, MSI Plessey, PostCode, Telepen          |                                                                                                                                                                               |
| 2D Barcode         | QR Code, Micro QR Code, PDF417, Micro PDF417, Grid Matrix, MaxiCode, Aztec Code, Data Matrix                                                                                     |                                                                                                                                                                               |
| Rotation           | Font and barcode support 0, 90, 180, 270 degree                                                                                                                                  |                                                                                                                                                                               |
| Printer language   | Compatible to TSPL, EPL, ZPL, ZPL II, DPL                                                                                                                                        |                                                                                                                                                                               |
| Physical dimension | 260mm (W) * 335mm (H) * 439mm (D)                                                                                                                                                |                                                                                                                                                                               |
| Net Weight         | 12.8kg                                                                                                                                                                           |                                                                                                                                                                               |

## Applications

· Logistics      · Shipping      · Manufacturing      · Retail      · Warehousing      · Transportation

### Environmental concern

Comply with RoHS, REACH, WEEE

### Environment condition

Operation: 5 ~ 40°C, 25 ~ 85% non-condensing  
Storage: -40 ~ 60°C, 10 ~ 90% non-condensing

### Safety regulation

FCC Class A, CE Class A, CCC, BIS, CB

### Accessories

- Windows labeling software CD disk
- Quick start guide
- USB cable
- Power cord
- 1" ribbon spindle x 2 for 450M ribbon

